



量程<10t: 线缆φ5.1×3m  
量程≥10t: 线缆φ5.1×10m



### 尺寸

量程	C	H1	H2	L	L1	L2	L3	L4	L5
<b>t/mm</b>									
2-5	35.0	11.5	16.0	105.0	20.0	12.0	12.0	35.0	6.30
10	50.0	20.0	22.5	152.0	30.0	18.0	18.0	48.0	10.5
20	65.0	22.5	28.5	190.0	32.0	20.0	25.0	65.0	10.5
40	85.0	22.5	28.5	256.0	36.0	35.0	28.0	89.0	12.5
70	100.0	34.0	35.0	328.0	40.0	50.0	32.0	120.0	15.0
100	120.0	44.0	45.0	328.0	40.0	50.0	32.0	120.0	15.0
<b>lb/inches (由上述尺寸转换)</b>									
4,409.2-11,023.1	1.38	0.45	0.63	4.13	0.79	0.47	0.47	1.38	0.25
22,046.2	1.97	0.79	0.89	5.98	1.18	0.71	0.71	1.89	0.41
44,092.5	2.56	0.89	1.12	7.48	1.26	0.79	0.98	2.56	0.41
88,184.9	3.35	0.89	1.12	10.08	1.42	1.38	1.10	3.50	0.49
154,323.6	3.94	1.34	1.38	12.91	1.57	1.97	1.26	4.72	0.59
220,462.3	4.72	1.73	1.77	12.91	1.57	1.97	1.26	4.72	0.59

### 技术参数

灵敏度	1.0 mV/V ± 10%	额定激励电压	10V (15V 最大)
零位输出	±0.02 mV/V	绝缘阻抗	>2 [ 50V DC ] GΩ
非线性	<±0.50%	正常工作温度范围	-10°C - 50°C / 14°F - 122°F
重复性	<±0.30%	安全极限载荷	150% 满量程
滞后误差	<±0.50%	破坏极限载荷	400% 满量程
蠕变	<±0.20%	密封方式	密封 / IP67
输入阻抗	400Ω ± 20	接线方式	Exc+ 红      Exc- 黑
输出阻抗	350Ω ± 3		Sig+ 绿      Sig- 白
原材料	2Cr13 不锈钢		屏蔽线

### 货号\*

量程	货号	毛重(kg)
2t.....	535TS-2t-YZ.....	0.8
5t.....	535TS-5t-YZ.....	0.8
10t.....	535TS-10t-YZ.....	2.1
20t.....	535TS-20t-YZ.....	4.6
40t.....	535TS-40t-YZ.....	11.2
70t.....	535TS-70t-YZ.....	20.0
100t.....	535TS-100t-YZ.....	30.0

\* ATEX, FM, IECEx 认证版本货号带有“-Ex”后缀

### 应用举例

